



PRODUCT DATA SHEET

One Step Polish & Sealant / O-123

VOC compliant

Features: *One Step Polish & Sealant* is a multi-purpose polish that cleans polishes and protects with a polymer shield. Outstanding for removal of factory paint blemishes.

Benefits: An economical labor saving product that removes oxidation, scratches and swirl marks while building a high gloss polymer protective coating.

Uses: All OEM factory paints and refinished paint surfaces over thirty days old.

Directions: Can be used with D.A. or Orbital polisher, high-speed buffer or hand applied.

- Hand Application Apply *One Step Polish & Sealant* to a wax applicator pad wipe onto all clean painted surfaces. Allow to dry 5-10 minutes-remove by wiping with a clean terry towel.
- Machine Application Use a VG-110-G Lamb's Wool or VG-500-G or VG-800-G foam pad. Set buffer speed at 1,250 to 1,750 rpm. Apply a stripe of *One Step Polish & Sealant* to one quarter of panel, spread product and buff until a lustrous shine appears. Remove residue with a soft terry towel.
- Orbital or Dual Action Polisher Apply stripes of product to a single area, i.e. hood, roof or trunk. Spread product and buff to polish surface. Move on to next panel, repeat. Remove residue with a soft terry towel.

Tips: Use only 2-4 ounces of product per vehicle when applying as a final sealant. Allow to dry 5-10 minutes before removal. **DO NOT APPLY TO BLACK PEBBLE TRIM.**

Sizes: VG-O123 = 12 pints per case
VG-O123G = 4 gallons per case



Automotive International, Inc. * 8855 Blue Ash Road * Cincinnati, OH 45242
Phone: 513.489.7883 * Fax: 513.489.1329 * Web Site: www.valugard.net